

**Technisches Merkblatt
Technical Report**

Distributed by

**PRODUCTS, INC.**contact@patproducts.com | www.patproducts.com**ROWAKRYL G-31797W**

APPLICATION :

- PVC-tarpaulins
- PVC-truck cover
- PVC-tent-roof

TECHNICAL DATA :

Delivery form: Dispersion, waterborne, white
Solid content - % : 22,5 ± 1,0
Flow time - sec : 45 ± 15
(4mm DIN cup)
Gloss at 60° : 75 ± 5
Resin System : Acrylic, PVC
Solvents included : Water, EDG

PROPERTIES :

- Non-Blocking
- Weather resistant
- Weldable
- Flexible
- Glossy

PROCESSING :

- **Mix well before use !**
- **Filter before application !**

Drying requirement : • 1 min / 100°C-120°C

Film thickness - g/m² dry : • 4 - 6

Application methods : • Rotogravure • Magnet bar

Additives :

- ROWASET 61521W (wetting agent)
- ROWASET 61247W (defoamer)
- ROWASET 61542W (thickener)

Storage :

- Room-temperature
- Original pack
- Keep from frost
- Keep from heat

Shelf life : • 6 month (Air-tight closed original packaging)

Update: 01.08.05 / PO
28.06.07 / IN